




Universal Hip & Ridge

DESCRIPTION

Seneca Shake™ Hip & Ridge is a rubber and plastic-based ridge tile designed to provide the look of natural stone slate in the ridge and hip portions of the roof. Used in conjunction with all Seneca Shake roofing tiles, Seneca Shake Hip & Ridge is manufactured with a state of the art formulation using recycled polyolefin polymers.

Seneca Shake Hip & Ridge is 12" wide, 18" long and ¼" thick and is available in eleven (11) colors.



ADVANTAGES

Seneca Shake Hip & Ridge provides the look of natural slate with these added advantages:

- High impact resistance which provides protection from hail, falling branches, foot traffic, ice and snow damage.
- Seneca Shake Hip & Ridge can be installed up to 8 times faster than natural stone slate.
- The color in Seneca Shake Hip & Ridge has been added during formulation providing for color throughout the product. As with all roofing products, natural weathering will occur.
- EcoStar provides warranties for Seneca Shake Hip & Ridge for up to 50 years.

LIMITATIONS

Color Variation – All Seneca Shake Hip & Ridge tiles come with shade variation. This shade variation may occur differently from pallet to pallet. Application of the product should not begin until all material has been delivered to the project site. Because of this shade variation the applicator must take precautions to ensure that the various shades of the product are properly blended. Tiles must be taken from different pallets and bundles to ensure consistency in application. **NOTE: EcoStar will not be responsible for the improper blending and application of the product.**

Natural weathering will produce further shade variations, even in tiles appearing to be identical in color when new.

INSTALLATION

Exposure – Hip & Ridge tiles are always installed with a 6" exposure.

Temperature – If tiles have been stored in temperatures below 45° F, it is required that the tiles be brought back to an ambient material temperature above 45° F before installation.

Substrate – Majestic Slate should only be installed on a minimum of ½" plywood, minimum 7/16" OSB or minimum ¾" tongue and groove wood decking. Majestic Slate should not be applied over existing roof materials. Existing roof materials must be removed down to the deck, prior to installation.

Fasteners – Fasteners must be ring shank stainless steel. **EcoStar Fasteners** are available in hand drive style in 2" and 2½" lengths.

Ventilation – At the same time the ridge tiles are being installed, roof venting should be installed. EcoStar's **EcoVent™** ridge venting is recommended for quality attic ventilation and an improved aesthetic appearance of the EcoStar roof system.

PRODUCT SPECIFICATIONS

FORMULATION		
Materials	Thermoplastic Olefin	
PRODUCT CHARACTERISTIC	Units	Results
Length	in.	18
Width	in.	12
Weight	lbs.	1.5 (nominal)
Thickness	in.	¼ (nominal)
Tiles per linear foot	2 at required 6" exposure	
PHYSICAL PROPERTIES	Units	Results
Operating Range	°F	-25° to 200°
Tensile (D-412)	psi	500
Water Absorption (D-570)	0% by wt.	
PACKAGING INFORMATION		
Tiles per bundle	10	
Weight per bundle	lbs.	15
Tiles per pallet	1000	
Weight per pallet	lbs.	1500
Linear feet per bundle	ft.	5

WARRANTIES

EcoStar warrants this product to be free of defects in workmanship and materials at the time of shipment from EcoStar's factory. EcoStar will at its option either supply new product or refund the purchase price of any product found to be defective hereunder.

EcoStar's limited warranties are the only warranties extended by EcoStar with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. EcoStar specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of EcoStar's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the EcoStar material in question.

*See www.ecostarllc.com for available warranties.



42 Edgewood Drive | Holland, NY 14080 | Tel: 800.211.7170 | www.ecostarllc.com

09/18 © Copyright 2018 EcoStar LLC. EcoStar, Seneca Shake and EcoVent are trademarks of EcoStar LLC.
P/N-606020 Seneca Shake Hip & Ridge PTD. This data sheet, effective 09/19/2018 supersedes all previous versions.

PRODUCT TECHNICAL DATA