



IMPROVED CERTIFICATIONS SEARCH TOOL. REGISTER NOW!

[LEARN MORE](#)

TFXX7.R18920

Prepared Roof-covering Materials, Formed or Molded Metal, Fiber-Cement, Plastic or Fire-retardant-treated Wood Certified for Canada

[Page Bottom](#)

Prepared Roof-covering Materials, Formed or Molded Metal, Fiber-Cement, Plastic or Fire-retardant-treated Wood Certified for Canada

[See General Information for Prepared Roof-covering Materials, Formed or Molded Metal, Fiber-Cement, Plastic or Fire-retardant-treated Wood Certified for Canada](#)

ECOSTAR LLC

42 EDGEWOOD DR
HOLLAND, NY 14080-9784 USA

R18920

Molded plastic shingles, for installation as Class A prepared roof covering. Limited to 15/32 in. plywood decks and one layer of G-P Gypsum, 1/4 in. (min) DensDeck® with all joints staggered a min of 6 in. from the plywood joints and one ply of Type 30 asphalt felt, or one ply of GAF VersaShield Fire Resistant Roof Deck Protection (one layer of UL Classified self-adhering underlayment may be optionally used under the VersaShield Underlayment) or Atlas Roofing "FR 50", covered with any one or combination of the following shingles: Majestic Slate Products ("Traditional", "Colonial", "Beveled Edge", "Beavertail", "Chisel Point"), Seneca Cedar Shake Products ("Seneca") or Titus Products ("Titus"). As an option, an additional layer of Aqua Guard underlayment or any UL Classified base sheet or underlayment product may be installed directly below the shingles.

Molded plastic shingles, for installation as Class A prepared roof covering. Limited to 15/32 in. plywood decks and one layer of G-P Gypsum, 1/4 in. (min) DensDeck® with all joints staggered a min of 6 in. from the plywood joints and one ply of Type 30 asphalt felt, or two plies of GAF VersaShield Fire Resistant Roof Deck Protection (one layer of UL Classified self-adhering underlayment may be optionally used under the VersaShield Underlayment) or Atlas Roofing "FR 50", covered with any one or combination of the following shingles: Seneca Cedar Shake Products ("Seneca Plus", "Thick Butt"). As an option, an additional layer of Aqua Guard underlayment or any UL Classified base sheet or underlayment product may be installed directly below the shingles.

Molded plastic shingles, for installation as Class C prepared roof covering. Limited to 15/32 in. plywood decks. Minimum one ply of Type 30 felt, covered with any one or combination of the following shingles: Majestic Slate Products ("Traditional", "Colonial", "Beveled Edge", "Beavertail", "Chisel Point"), Seneca Cedar Shake Products ("Seneca", "Seneca Plus", "Thick Butt"), Titus Products ("Titus") or Empire Slate Products ("Traditional", "Beveled Edge", "Beavertail", "Chisel Point"). As an option, an additional layer of Aqua Guard underlayment or any UL Classified base sheet or underlayment product may be installed directly below the shingles.

Molded plastic shingles, designated "Majestic Slate Colonial", "Majestic Beveled Edge Slate", "Majestic Beavertail Slate", "Majestic Slate Traditional" or "Majestic Chisel Point Slate" may be also bear the statement "Degree of wind resistance investigated in accordance with procedures adapted from ASTM D3161 at a wind speed of 110 mph". Limited to a max. 7 in. exposure with a min. 3 in. x 10 in. strip of "Sure-Seal SecurTape" applied to the backside of the shingle.

Molded plastic shingles, designated "Majestic Slate Colonial", "Majestic Beveled Edge Slate", "Majestic Beavertail Slate", "Majestic Slate Traditional" or "Majestic Chisel Point Slate" may be also bear the statement "Degree of wind resistance investigated in accordance with procedures adapted from ASTM D3161 at a wind speed of 110 mph". Limited to a max. 7 in. exposure with a min. 1/4 in. bead, 10 in. long of the Dow Corning "790 Silicone Building Sealant" applied to the backside of the shingle.

Molded plastic shingles, designated "Seneca Cedar Shake Tiles", "Seneca Plus Shake" or "Seneca Shake Thick Butt Design" may be also bear the statement "Degree of wind resistance investigated in accordance with procedures adapted from ASTM D3161 at a wind speed of 110 mph". Limited to a max. 8 in. exposure with a min. 1/4 in. bead of the Dow Corning "790 Silicone Building Sealant" applied to the backside of the shingle, within 1 in. of each side of the shingle.

Molded plastic shingles, designated "Seneca Shake Thick Butt Design" or "Seneca Plus Shake" may be also bear the statement "Degree of wind resistance investigated in accordance with procedures adapted from ASTM D3161 at a wind speed of 110 mph". Limited to a max. 8 in. exposure.

Molded plastic shingles, for installation as Class A prepared roof covering. Limited to 15/32 in. plywood decks and one layer of G-P Gypsum, 1/4 in. (min) DensDeck® with all joints staggered a min of 6 in. from the plywood joints and one ply of Type 30 asphalt felt, or one ply of VersaShield Fire Resistant Roof Deck Protection (one layer of UL Classified self-adhering underlayment may be optionally used under the VersaShield Underlayment) or Atlas Roofing "FR 50", covered with any one or combination of the following shingles: Empire Slate Products ("Traditional", "Beveled Edge", "Beavertail", "Chisel Point"). As an option, an additional layer of Aqua Guard underlayment or any UL Classified base sheet or underlayment product may be installed directly below the shingles.

Molded plastic shingles, designated "Empire Beveled Edge Slate", "Empire Beavertail Slate", "Empire Slate Traditional" or "Empire Chisel Point Slate" may be also bear the statement "Degree of wind resistance investigated in accordance with procedures adapted from ASTM D3161 at a wind speed of 110 mph". Limited to a max. 6 in. exposure with a min. 1/4 in. bead, 10 in. long of the Dow Corning "790 Silicone Building Sealant" applied to the backside of the shingle.

Molded plastic shingles, for installation as Class A prepared roof covering. Limited to 15/32 in. plywood decks and one ply of GAF VersaShield Fire Resistant Roof Deck Protection covered with "Empire Niagara". May also bear the statement "Degree of wind resistance investigated in accordance

with procedures adapted from ASTM D3161 at a wind speed of 110 mph". Limited to a max. 10 in. exposure with a min. 1/4 in. bead, 10 in. long of the Dow Corning "790 Silicone Building Sealant" applied to the backside of the shingle.

Molded plastic shingles, for installation as Class C prepared roof covering. Limited to 15/32 in. plywood decks and one ply of Type G2, covered with "Empire Niagara". May also bear the statement "Degree of wind resistance investigated in accordance with procedures adapted from ASTM D3161 at a wind speed of 110 mph". Limited to a max. 10 in. exposure with a min. 1/4 in. bead, 10 in. long of the Dow Corning "790 Silicone Building Sealant" applied to the backside of the shingle.

Molded plastic shingles, for installation as Class C prepared roof covering. Limited to 15/32 in. plywood decks and one ply of Type 30, covered with "Majestic Niagara Slate". May also bear the statement "Degree of wind resistance investigated in accordance with procedures adapted from ASTM D3161 at a wind speed of 110 mph". Limited to a max. 10 in. exposure with a min. 1/4 in. bead, 10 in. long of the Dow Corning "790 Silicone Building Sealant" applied to the backside of the shingle.

Last Updated on 2017-02-01

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".