



Roofing Underlayment

DESCRIPTION

Aqua Guard™ is a reinforced polyolefin composite sheeting material designed to offer speedy installation. As a roof underlayment, Aqua Guard provides superior protection for the building interior while offering a stronger and lighter alternative to the traditional felt underlayment. A versatile product, Aqua Guard resists deterioration in extreme temperatures and is highly resistant to wind blow off.

INSTALLATION

It is recommended that Aqua Guard be installed by professional roofing applicators to ensure a quality installation.

Prior to installation, the roof deck must be clean, smooth and dry. Because Aqua Guard is considered a vapor barrier, EcoStar recommends that it be installed above vented attic spaces. For further assistance, contact EcoStar's Technical Department.

Aqua Guard is laid out horizontally with printed side up using 4" (102 mm) horizontal laps and 6" (152 mm) vertical laps. For prolonged exposure where driving rain or strong winds are expected it is recommended to double the overlaps.

Aqua Guard should be installed with plastic or metal (ring shank or smooth shank) cap-nails or cap-staples. For short term coverage (48 hours) Aqua Guard can be fastened using every other anchoring position as printed on the product. For extended exposure fasten the product using every anchoring position as printed on the product. All anchoring must be performed flush to the roof, 90° to the roof deck that will hold the material tightly with the plywood. Product has 180 days UV protection, but it should not be considered a final roofing system. A proper final roofing system should be installed over the product to get the proper protection.

ADVANTAGES

Aqua Guard is ideal for both residential and commercial applications in both new construction and re-roofing jobs. It is a cost-effective material that does not tear easily or degrade from exposure to the elements when used as intended. Aqua Guard provides an ideal installation, being both easy on the back as well as highly slip resistant. Aqua Guard also meets all national building codes.

TYPICAL PROPERTIES

FORMULATION	
Material	Polyolefin
PRODUCT CHARACTERISTIC	
Roll Length	250 ft. (76.2 m)
Roll Width	48 in. (1.22 m)
Roll Weight	35 lbs. (15.9 kg)
Square Feet/Roll	1,000
PHYSICAL PROPERTIES (Typical)	
Operating Range	-40° F (-40° C) to 240° F (116° C)
PACKAGING	
Boxes (Rolls) per Pallet	36
Weight per Pallet (including pallet)	1,340 lbs. (572 kg)
APPLICABLE STANDARDS	
Breaking Strength ASTM D 5034 MD	164 lb (74 kg)
Breaking Strength ASTM D 5034 CD	152 lb (69 kg)
Tear Strength ASTM D4533 MD	40 lb (18kg)
Tear Strength ASTM D4533 CD	37 lb (17 kg)
Water shower Exposure ASTM D 4869	Pass
Nominal Thickness ASTM D1777	20 mils
Mullen Burst	156 psi

APPROVALS

- Miami-Dade County Approved NOA 16-0510.30
- Florida Building Code Approved FL20853
- Texas Department of Insurance

WARRANTIES

EcoStar warrants this product to be free of defects in workmanship and materials at the time of shipment from EcoStar's factory. EcoStar will at its option either supply new product or refund the purchase price of any product found to be defective hereunder.

EcoStar's limited warranties are the only warranties extended by EcoStar with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. EcoStar specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of EcoStar's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the EcoStar material in question.



42 Edgewood Drive | Holland, NY 14080 | Tel: 800.211.7170 | www.ecostarllc.com

06/19 © Copyright 2019 EcoStar LLC. EcoStar and Aqua Guard a trademark of EcoStar LLC.
P/N-602712 Aqua Guard Technical Data Sheet. This data sheet, effective 06/05/2019, supersedes all previous versions.

PRODUCT TECHNICAL DATA