

UL Evaluation Report

UL ER18920-02

Issued: March 31, 2017

Revised: December 13, 2019

Visit UL, LLC's [Product iQ™ database](#) for the status of this Report.

UL Category Code: ULEZ

CSI MasterFormat®

DIVISION: 07 00 00 - THERMAL AND MOISTURE PROTECTION

Sub-level 2: 07 30 00 - Steep Slope Roofing

Sub-level 3: 07 31 00 - Shingles and Shakes

Sub-level 4: 07 31 53 - Plastic Shakes

Sub-level 3: 07 32 00 - Roof Tiles

Sub-level 4: 07 32 26 - Plastic Roof Tiles

COMPANY:

ECOSTAR LLC
42 EDGEWOOD DRIVE
HOLLAND, NEW YORK 14080
(800) 211-7170
www.ecostarllc.com

1. SUBJECT:

MAJESTIC SLATE, MAJESTIC NIAGARA SLATE, AND SENECA SHAKE POLYOLEFIN COMPOSITE ROOF TILES

2. SCOPE OF EVALUATION:

- 2018, 2015, and 2012 *International Building Code*® (IBC)
- 2018, 2015, and 2012 *International Residential Code*® (IRC)
- ICC-ES Acceptance Criteria for Special Roofing Systems (AC07)
- ICC-ES Acceptance Criteria for Quality Documentation (AC10)



The products were evaluated for the following properties:

- Uplift Resistance (ANSI/UL 580)
- Roofing Systems for Exterior Fire Exposure (ANSI/UL790, ASTM E108)
- As Required in AC07 for Plastic Tiles and Panels

3. REFERENCED DOCUMENTS

- ICC-ES:
 - ICC-ES Acceptance Criteria for Foam Plastic Insulation (AC07), dated February 2014 with revisions through April 2018
 - ICC-ES Acceptance Criteria for Quality Documentation (AC10), dated January 2019
- ANSI/UL:
 - ANSI/UL 580, Fifth Edition, Standard for Tests for Uplift Resistance of Roof Assemblies
 - ANSI/UL790, Eighth Edition (ASTM E108), Standard Test Methods for Fire Tests of Roof Coverings

4. USES

Majestic Slate, Majestic Niagara Slate, and Seneca Shake tiles are used as roof covering materials in Class A or Class C roofing systems when installed in accordance with this report and the manufacturer's published installation instructions.

5. PRODUCT DESCRIPTION

The EcoStar Majestic Slate, Majestic Niagara Slate, and Seneca Shake series products described in this report are synthetic composite roofing tiles manufactured using virgin and recycled polyolefin polymers. The Majestic Slate tiles are available in Traditional, Beaver Tail, Beveled Edge, and Chisel Point. Seneca tiles are provided in 12", 9", and 6" widths packaged in a 1:2:1 ratio in standard and Plus (Thick Butt) thicknesses. Accompanying hip and ridge products are available in standard sizes and thicknesses.

Fire Classification: EcoStar synthetic composite roofing tiles covered under this report have been tested for fire classifications Class A and Class C in accordance with ANSI/UL790 (ASTM E108) and qualify for use under [Section 1505.1](#) of the 2018, 2015, and 2012 IBC and [Section R902.1](#) of the 2018, 2015, and 2012 IRC . Refer to Table 1.

Wind Resistance: Roofing assemblies shall be designed to resist the design wind load pressures for components and cladding in accordance with [Chapter 16](#) and [Section 1504.3](#) of the 2018, 2015, and 2012 IBC and [Section R905.1](#) of the 2018, 2015, and 2012 IRC .

Wind Uplift Resistance: EcoStar synthetic composite roofing tiles covered under this report have been tested for wind uplift resistance in accordance with ANSI/UL 580/1897. Refer to Table 1.

Physical Properties: EcoStar composite roofing tiles covered under this report have been tested as Type I molded specimens, both as manufactured and Xenon Arc weathered, for tensile properties in accordance with ASTM D638, flexural properties in accordance with ASTM D790, and for temperature cycling as specified in AC07.

6. INSTALLATION

6.1 General:

Installation of EcoStar composite roofing tiles must be installed in accordance with [Section 1507.7](#) of the 2018, 2015, and 2012 IBC or [Section R905.6](#) of the 2018, 2015, and 2012 IRC , except as noted in this report, and the manufacturer's published installation instructions. The manufacturer's published installation instructions must be available at all times on the jobsite during installation. The composite roofing tiles must be attached to the decked sheathing in a manner that will secure the tiles in place.

6.2 Slope:

Minimum slope of substrate for installation of Majestic Slate is 3:12 for 6 inch exposure, and 6:12 for 7 inch exposure. Minimum slope of substrate for installation of Seneca Shake is 3:12 for 7 inch exposure and 6:12 for 8 inch exposure. Minimum slope of substrate for installation of Majestic Niagara Slate is from 3:12 to 6:12 for 9 inch exposure and 6:12 or greater for 9 or 10 inch exposures.

6.3 Sheathing:

The minimum required sheathing is to be nominal ½ inch wood decking. The sheathing must be structurally sound and adequately fastened to resist wind loads for components and cladding as specified in [Section 1609](#) of the 2018, 2015, and 2012 IBC and [Section R301.6](#) of the 2018, 2015, and 2012 IRC .

6.4 Underlayment:

An ice barrier must be installed along the eaves in locations historically prone to ice in accordance with [Section 1507.7.4](#) of the 2018, 2015, and 2012 IBC and [Section 905.6.3.1](#) of the 2018, 2015, and 2012 IRC. In addition to the ice barrier, an underlayment must be installed over the entire roof deck in accordance with [Section 1507.7.3](#) of the 2018, 2015, and 2012 IBC and [Section R905.6.3](#) of the 2018, 2015, and 2012 IRC .

6.5 Flashing:

Flashing materials are to be installed in accordance with [Section 1503.2](#) and [Section 1507.7.7](#) of the 2018, 2015, and 2012 IBC and [Section R903.2](#) and [Section R905.6.6](#) of the 2018, 2015, and 2012 IRC , as applicable.

6.6 Roofing Tiles:

Installation of the composite roofing tiles must begin at the eave edge with a starter row. An overlaying offset row is then installed to cover the starter row nail heads. Subsequent courses to be installed in accordance with the manufacturer's instructions.

6.7 Hips and Ridges:

Hips and ridges must be installed in accordance with EcoStar, LLC's published installation instructions for exposure dimension and fastener type.

6.8 Fasteners:

EcoStar supplied fasteners are minimum 1-1/2 inch long stainless steel ring-shanked nails for Majestic Slate and Seneca Shake. EcoStar supplied fasteners are minimum 1-3/4 inch long stainless steel ring-shanked nails for Majestic Niagara Slate. The nails have heads of 3/8 inch in diameter with 0.121 inch diameter shanks.

6.9 Reroofing:

Existing roof covering materials are to be removed prior to installation of the EcoStar composite roofing tiles. Installation is to be performed for new construction as described in Section 6 of this report.

7. CONDITIONS OF USE

7.1 General:

The composite roofing tiles described in this report comply with, or are suitable alternatives to, what is specified in those codes listed in Section 2 of this report, subject to the following conditions:

- 7.2** Materials and methods of installation shall comply with this report and the manufacturer's published installation instructions. In the event of a conflict between the installation instructions and this report, this report governs.
- 7.3** Only EcoStar specified fasteners shall be used in the installation of the roof covering system.
- 7.4** See the UL [Product iQ™ database](#) for Prepared Roof Covering Materials, Formed or Molded Metal, Fiber-Cement, Plastic or Fire-retardant-treated Wood ([TFXX](#)), Roof-covering Materials, Impact Resistance ([TGAM](#)), and ([TGIK](#)), Roofing Systems, Uplift Resistance.
- 7.5** Wind uplift pressures on any roof area, including edges and corner zones shall not exceed the allowable wind pressure for the roof covering installed in that particular area. The allowable wind uplift pressure for the roof assembly shall be based on a minimum factor of safety of 2.0. A safety factor of 2.0 must be applied to the rating for uplift resistance. The allowable wind uplift pressure is for the roof system only. The deck and framing to which the roofing system is attached shall be designed for the applicable component and cladding, wind loads in accordance with the applicable code.
- 7.6** The Majestic Slate, Majestic Niagara Slate, and Seneca Shake composite roofing tiles covered under this report are produced by EcoStar, LLC in Holland, New York under the UL LLC Listing/Classification and Follow-Up Service Program, which includes audits in accordance with quality elements of ICC-ES Acceptance Criteria for Quality Documentation, AC10.
- 7.7** Reroofing must be in accordance with Section 6.9 of this report.

8. SUPPORTING EVIDENCE

- 8.1** Data in accordance with ICC-ES Acceptance Criteria for Special Roofing Systems (AC07), dated February 2014.
- 8.2** Documentation of quality system elements described in ICC-ES Acceptance Criteria for Quality Documentation (AC10), dated December 2014.
- 8.3** UL Classification reports in accordance with ANSI/UL 790, and UL 2218. See UL Product Certification Categories (TFXX) and (TGAM), respectively.

9. IDENTIFICATION

EcoStar composite roofing tiles described in this evaluation report are identified by a marking bearing the report holder's name (EcoStar,LLC) and address, the product name, the ASTM type designation, the UL Certification Mark where applicable, and the evaluation report number UL ER18920-02. The validity of the evaluation report is contingent upon this identification appearing on the product or UL Classification Mark certificate.

10. USE OF UL EVALUATION REPORT

- 10.1 The approval of building products, materials or systems is under the responsibility of the applicable authorities having jurisdiction.
- 10.2 UL Evaluation Reports shall not be used in any manner that implies an endorsement of the product, material or system by UL.
- 10.3 The status of this report, as well as a complete directory of UL Evaluation Reports may be found at UL.com via the [Product iQ™ database](#).

TABLE 1: COMBUSTIBLE DECK ASSEMBLIES

System No.	Composite Roof Tile Attachment	Underlayment/Barrier Board Configuration	Deck	Deck Attachment ¹	Wind Uplift		Fire Rating (Unlimited Incline) ³
					Tested Pressure (psf)	Maximum Design Pressure ²	
MAJESTIC SLATE					ANSI/UL 1897		ANSI/UL 790
1	Two 1-½ inch by 0.12 inch ring shank nails, 7 inch exposure	Minimum ¼ inch Georgia-Pacific Gypsum, LLC DensDeck mechanically fastened ⁴ and one ply Type 30 asphaltic felt, or one ply of: GAF VersaShield, or Atlas FR 50 ⁵	Minimum ¹⁵ / ₃₂ APA rated plywood Type C-D ⁶ or minimum ⁷ / ₁₆ APA PS2 OSB	8d annular ring-shank nails 6 inch on center	-135	-67.5	Class A
2	Three 1-½ inch by 0.12 inch ring shank nails, 7 inch exposure			8d annular ring-shank nails 6 inch on center	-180	-90	
3	Two 1-½ inch by 0.12 inch ring shank nails, 7 inch exposure ⁷		Minimum ¹⁵ / ₃₂ APA rated CDX plywood	0.113 x 2- ³ / ₈ inch long annular ring-shank nails 6 inch on center	-225	-112.5	
4	Four 1-½ inch by 0.12 inch ring shank nails, 7 inch exposure ⁷			0.113 x 2- ³ / ₈ inch long annular ring-shank nails 6 inch on center	-255	-127.5	
5	Two 1-½ inch by 0.12 inch ring shank nails, 7 inch exposure ⁷		Minimum ¹⁹ / ₃₂ APA rated CDX plywood	0.113 x 2- ³ / ₈ inch long annular ring-shank nails 6 inch on center	-210	-105	

¹Nominal 2 inch dimensional framing lumber spaced 24 inches on center.

²The maximum design wind uplift pressure utilizes a safety factor of 2 to the maximum tested load achieved without failure.

³Class C Fire Rating achieved by substituting one ply Type 30 asphaltic felt for the underlayment/barrier board in any of the above assemblies.

⁴Refer to Georgia-Pacific Gypsum, LLC's website for preliminary fastening patterns for mechanically attached roof coverings.

⁵One layer of any UL Classified self-adhering underlayment optional underneath the underlayment/barrier board.

⁶Refer to Guide Information for [Prepared Roof-Covering Materials, Formed or Molded Metal, Fiber-Cement, Plastic or Fire-retardant-treated Wood](#).

⁷³/₈-inch wide gap between adjacent roofing slates with courses offset one half tile width.

TABLE 1: COMBUSTIBLE DECK ASSEMBLIES (continued)

System No.	Composite Roof Tile Attachment	Underlayment/Barrier Board Configuration	Deck	Deck Attachment	Wind Uplift		Fire Rating (Unlimited Incline) ²
					Tested Pressure (psf)	Maximum Design Pressure ¹	
MAJESTIC SLATE					ANSI/UL 1897		ANSI/UL 790
6	Four 1-½ inch by 0.12 inch ring shank nails, 7 inch exposure ³	Minimum ¼ inch Georgia-Pacific Gypsum, LLC DensDeck mechanically fastened ⁴ and one ply Type 30 asphaltic felt, or one ply of: GAF VersaShield, or Atlas FR 50 ⁵	Minimum ¹⁹ / ₃₂ APA rated CDX plywood	0.113 x 2-¾ inch long annular ring-shank nails 6 inch on center	-345	-172.5	Class A
SENECA SHAKE					ANSI/UL 1897		ANSI/UL 790
7	Two 1-½ inch by 0.12 inch ring shank nails, 8 inch exposure	Minimum ¼ inch Georgia-Pacific Gypsum, LLC DensDeck mechanically fastened ⁵ and one ply Type 30 asphaltic felt, or one ply of: GAF VersaShield, or Atlas FR 50 ⁶	Minimum ¹⁵ / ₃₂ APA rated plywood Type C-D ⁷ or minimum ⁷ / ₁₆ APA PS2 OSB	8d annular ring-shank nails 6 inch on center	-135	-67.5	Class A
8	Three 1-½ inch by 0.12 inch ring shank nails, 8 inch exposure			8d annular ring-shank nails 6 inch on center	-150	-75	
9	Two 1-½ inch by 0.12 inch ring shank nails, 8 inch exposure ⁸		Minimum ¹⁵ / ₃₂ APA rated CDX plywood	0.113 x 2-¾ inch long annular ring-shank nails 6 inch on center	-165	-82.5	

¹Nominal 2 inch dimensional framing lumber spaced 24 inches on center.

²The maximum design wind uplift pressure utilizes a safety factor of 2 to the maximum tested load achieved without failure.

³Class C Fire Rating achieved by substituting one ply Type 30 asphaltic felt for the underlayment/barrier board in any of the above assemblies.

⁴¾-inch wide gap between adjacent roofing slates with courses offset one half tile width.

⁵Refer to Georgia-Pacific Gypsum, LLC's website for preliminary fastening patterns for mechanically attached roof coverings.

⁶One layer of any UL Classified self-adhering underlayment optional underneath the underlayment/barrier board.

⁷Refer to Guide Information for [Prepared Roof-Covering Materials, Formed or Molded Metal, Fiber-Cement, Plastic or Fire-retardant-treated Wood](#).

⁸¾-inch wide gap between adjacent roofing slates.

TABLE 1: COMBUSTIBLE DECK ASSEMBLIES (continued)

System No.	Composite Roof Tile Attachment	Underlayment/Barrier Board Configuration	Deck	Deck Attachment ¹	Wind Uplift		Fire Rating (Unlimited Incline) ³
					Tested Pressure (psf)	Maximum Design Pressure ²	
SENECA SHAKE					ANSI/UL 1897		ANSI/UL 790
10	Four 1-½ inch by 0.12 inch ring shank nails, 8 inch exposure	Minimum ¼ inch Georgia-Pacific Gypsum, LLC DensDeck mechanically fastened ⁴ and one ply Type 30 asphaltic felt, or one ply of: GAF VersaShield, or Atlas FR 50 ⁵	Minimum ¹⁵ / ₃₂ APA rated CDX plywood	0.113 x 2-¾ inch long annular ring-shank nails 6 inch on center	-225	-112.5	Class A
11	Two 1-½ inch by 0.12 inch ring shank nails, 8 inch exposure ⁶			0.113 x 2-¾ inch long annular ring-shank nails 6 inch on center	-210	-105	
12	Four 1-½ inch by 0.12 inch ring shank nails, 8 inch exposure ⁶			Minimum ¹⁹ / ₃₂ APA rated CDX plywood	0.113 x 2-¾ inch long annular ring-shank nails 6 inch on center	-360	

¹Nominal 2 inch dimensional framing lumber spaced 24 inches on center.

²The maximum design wind uplift pressure utilizes a safety factor of 2 to the maximum tested load achieved without failure.

³Class C Fire Rating achieved by substituting one ply Type 30 asphaltic felt for the underlayment/barrier board in any of the above assemblies.

⁴Refer to Georgia-Pacific Gypsum, LLC's website for preliminary fastening patterns for mechanically attached roof coverings.

⁵One layer of any UL Classified self-adhering underlayment optional underneath the underlayment/barrier board.

⁶¾-inch wide gap between adjacent roofing slates.

TABLE 1: COMBUSTIBLE DECK ASSEMBLIES (continued)

System No.	Composite Roof Tile Attachment	Underlayment/Barrier Board Configuration	Deck	Deck Attachment	Wind Uplift		Fire Rating (Unlimited Incline)
					Tested Pressure (psf)	Maximum Design Pressure ¹	
MAJESTIC NIAGARA SLATE					ANSI/UL 1897		ANSI/UL 790
13	Two 1- ³ / ₄ inch by 0.12 inch ring shank roofing nails, 10 inch exposure ²	Minimum one ply Type 30 asphaltic felt, mechanically fastened ^{3, 4}	Minimum ⁷ / ₁₆ APA PS2 OSB	0.113 x 2- ³ / ₈ inch long annular ring-shank nails 6 inch on center	-90	-45	Class C
14	Four 1- ³ / ₄ inch by 0.12 inch ring shank roofing nails, 10 inch exposure ²			0.113 x 2- ³ / ₈ inch long annular ring-shank nails 6 inch on center	-180	-90	
15	Two 1- ³ / ₄ inch by 0.12 inch ring shank roofing nails, 10 inch exposure ²		Minimum ¹⁵ / ₃₂ APA rated CDX plywood	0.113 x 2- ³ / ₈ inch long annular ring-shank nails 6 inch on center	-150	-75	
16	Four 1- ³ / ₄ inch by 0.12 inch ring shank roofing nails, 10 inch exposure ²			0.113 x 2- ³ / ₈ inch long annular ring-shank nails 6 inch on center	-285	-142.5	
17	Two 1- ³ / ₄ inch by 0.12 inch ring shank roofing nails, 10 inch exposure ²		Minimum ¹⁹ / ₃₂ APA rated CDX plywood	0.113 x 2- ³ / ₈ inch long annular ring-shank nails 6 inch on center	-210	-105	
18	Four 1- ³ / ₄ inch by 0.12 inch ring shank roofing nails, 10 inch exposure ²			0.113 x 2- ³ / ₈ inch long annular ring-shank nails 6 inch on center	-240	-120	

¹The maximum design wind uplift pressure utilizes a safety factor of 2 to the maximum tested load achieved without failure.

²³/₈-inch wide gap between adjacent roofing slates with courses offset one half tile width.

³12 ga. 1-¹/₄ inch long ring shank nails with 32 ga. 1-⁵/₈ inch diameter tin caps 6 inches oc in 4 inch side lap and two staggered field rows 12 inches oc

⁴One layer of any UL Classified self-adhering underlayment optional underneath the underlayment/barrier board.

www.ul.com/erdirectory

2019 UL LLC

This UL Evaluation Report is not an endorsement or recommendation for use of the subject and/or product described herein. This report is not the UL Listing or UL Classification Report that covers the subject product. The subject product's UL Listing or UL Classification is covered under a separate UL Report. UL disclaims all representations and warranties whether express or implied, with respect to this report and the subject or product described herein. Contents of this report may be based on data that has been generated by laboratories other than UL that are accredited as complying with ISO/IEC Standard 17025 by the International Accreditation Service (IAS) or by any other accreditation body that is a signatory to the International Laboratory Accreditation Cooperation (ILAC) Mutual Recognition Arrangement (MRA). The scope of the laboratory's accreditation shall include the specific type of testing covered in the test report. As the accuracy of any non-UL data is the responsibility of the accredited laboratory, UL does not accept responsibility for the accuracy of this data.

